



ARDEX ACP 10

Tile and Grout Finishing Sealer

Preserve the natural look of your tiles

Does not change the appearance of the tile

Non yellowing

UV resistant

For internal and external applications

Low VOC content

ARDEX Australia Pty Ltd

20 Powers Road
Seven Hills NSW 2147
Phone: 1300 788 780
Fax: 1300 780 102
Email: technicalservices@ardexaustralia.com
Internet: www.ardexaustralia.com

ARDEX New Zealand Ltd

32 Lane Street
Woolston, Christchurch 8231
Phone: 0800 227 339
Fax: (03) 3849779
Email: info@ardexnz.com
Internet: www.ardex.co.nz

ARDEX ACP 10

Tile and Grout Finishing Sealer

DESCRIPTION

ARDEX ACP 10 Tile and Grout Finishing Sealer is a natural look water based penetrating sealer. It maintains the natural appearance of the surface whilst offering superior stain resistance of both oil and water based stains making sealed areas easier to clean. Suitable for indoor and outdoor use with excellent UV resistance and non yellowing.

ARDEX ACP 10 Tile and Grout Finishing Sealer is suitable over a wide range of surfaces.

SUITABLE SURFACES

Internal and external ceramic tiles, porcelain tiles, quarry tiles, slate, stone, terracotta, terrazzo, granite, cement, pavers, polished and stenciled concrete, cement based grout, dispersion grouts.

SURFACE PREPARATION

All surfaces must be cleaned free from dust, dirt, grease, oil, previous surface coatings and adhesive and other surface contaminants. Any surface contamination, surface irregularities or stains existing at the time of coating will be evident and locked in to the final finish. Test sealer in a small inconspicuous area to determine suitability for the project.

APPLICATION

1. Apply sealer by brush, roller or a low volume spray applicator.
2. Care should be taken not to apply excess material in each coat. Any material that has not penetrated into the surface after 10 minutes should be removed with a cloth. The number of coats required will vary depending on the porosity of the surface. Allow 30 minutes drying time between subsequent coats.
3. Most surfaces will require two coats however porous surfaces may require additional coats to sufficiently seal pores.

DRYING TIME

Allow 30 minutes to 1 hour drying time between coats. Allow 24 hours curing before subjecting to light pedestrian traffic, 3 days for rubber wheeled traffic and 7 days for full cure and maximum traffic loading.

COVERAGE

4L of ARDEX ACP 10 Tile and Grout Finishing Sealer will cover approximately 80m² per coat depending on the porosity of the surface and application technique.

CLEAN UP

Clean all equipment in warm water or water/detergent immediately on completion of project.

PACKAGING

ARDEX ACP 10 Tile and Grout Finishing Sealer is available in a 1L and 4L container.

SHELF LIFE

A shelf life of 2 years is expected when stored in an unopened container at 23°C.

PRECAUTIONS

ARDEX ACP 10 Tile and Grout Finishing Sealer will repel stains from spills that are cleaned up immediately. If a stain is left in place for an extended period the sealer's ability to repel the stain is reduced. The sealer will not waterproof the surface being sealed. This sealer is not recommended for use around swimming pools due to the various chemicals possibly found in swimming pools.

SAFETY

This product is classified as non-hazardous. Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and eye protection and keep the product out of the reach of children. Avoid inhalation of vapours, in case of ingestion immediately give a glass of water.

To ensure you have the most current technical data for product application please visit www.ardexaustralia.com. SDS available at www.ardexaustralia.com